



WEATHER SEAL

AQUA Tite Weather Seal is a nontoxic, non-flammable, penetrating surface sealer that completely seals and waterproofs most concrete, stamped concrete, brick, cured asphalt, stucco and sandstone surfaces. It is effective on both above and below grade surfaces. Weather Seal can be used alone, as a single product or it can be used in conjunction with AQUA Tite Moisture Blocker – an internal densifier and hardener that also waterproofs and reduces vapor transmission.

Make your space AQUA Tite

1 GALLON (3.785 LITERS)

MADE IN THE USA



SURFACE PREPARATION:

Do not apply to uncured concrete or asphalt. Normal surfaces require no special preparation, but the surface must be dry and free of dust, grease, oil and other foreign matter, such as previous coatings of paint. For best results, apply Weather Seal over Moisture Blocker. On new concrete, flush efflorescence and laitance should be removed. Where oil or grease has penetrated below the surface use a suitable cleaner and flush. Technical assistance is available for proper preparation. Weather Seal will seal small cracks that do not penetrate through the entire depth of the concrete. Large cracks should be filled with a suitable permanent concrete filler according to the manufacturer's instructions. **Ensure all surfaces are perfectly dry.**

APPLICATION INSTRUCTIONS:

1. Do not apply below 32°F. 2. For new concrete, wait 28 days to apply Weather Seal UNLESS the concrete has been treated with Moisture Blocker. 3. Apply as supplied, do not thin. 4. Shake well before using. 5. Apply with a low pressure sprayer or pour from bottle and evenly distribute with a push broom. 6. Apply liberally being sure to saturate all areas completely. On vertical walls, apply from the bottom up. On slabs, work material in with a soft mop for maximum penetration. 7. **Apply only one coat!** Do not attempt to apply a second coat. 8. **Do not allow to dry in "puddles" - spread puddles out with mop or broom before they dry.** 9. Weather Seal sets in 2-4 hours. Limited foot traffic is permissible after 30 minutes. 10. Clean tools with water. **DO NOT ATTEMPT A SECOND COATING. DO NOT apply to uncured concrete or asphalt. Do Not Apply to hot concrete in direct sun. Paints, coatings, epoxy, caulking, overlayments etc. will not bond well to Weather Seal.** If the sealer is frozen, allow to thaw before using and shake to mix well. Freezing will not harm the product.

COVERAGE: (Actual coverage will depend upon porosity of surface.) 1 Gallon treats 150-200 sq. ft.

WARNING: May cause an allergic reaction. May cause eye or skin irritation. May be harmful if swallowed.

FIRST AID TREATMENT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, seek medical attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, seek medical advice. Wash contaminated clothes before wearing again. IF SWALLOWED: Rinse mouth and throat thoroughly with water. Call POISON CONTROL or seek medical advice if you feel unwell. Keep out of reach of children.

For further safety information, please refer to the Safety Data Sheets available at www.aquatiteusa.com

SHAKE WELL BEFORE USING.

Distributed by:

Manufactured by:



235 WEST ROAD STE 3
PORTSMOUTH, NH 03801
1-603-431-5555

- ◆ Non-Toxic
- ◆ Non-Flammable
- ◆ Fumeless
- ◆ Safe
- ◆ Easy To Use